## **2026 RENEGADE X xc**



## **PACKAGE HIGHLIGHTS**

- Tri-Mode Dynamic Power Steering (DPS™)
- Intelligent Engine Braking (iEB™)
- · Visco-Lok† QE auto-locking front differential
- FOX<sup>†</sup> 1.5 PODIUM<sup>†</sup> RC2 shocks
- · Front & central skid plate
- Aluminum taper-profile handlebar with full wrap handguards
- X-package coloration, graphics and seat cover

ENGINE	1000K		
Туре	91 hp, Rotax® 976 cc V-twin, liquid-cooled		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT L/H/N/R/P		
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential		
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB)		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with sway bar 9.2 in. (23.3 cm) travel		
Front Shocks	FOX 1.5 PODIUM† RC2		
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel		
Rear Shocks	FOX 1.5 PODIUM <sup>†</sup> RC2		
TIRES & WHEELS			
Front / Rear Tires	ITP Holeshot† ATR 25 x 8/11 x 12 in.		
Wheels	12 in. aluminum beadlock		
BRAKES			
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers		

FNGINE

Rear

1000R	DIMENSIONS & CAPACITIES	
91 hp, Rotax® 976 cc V-twin, liquid-cooled	Estimated Dry	795 lb (361 kg)
Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Weight* LxWxH	86 x 48 x 49 in.
CVT		(218.4 x 121.9 x 124 cm)
L/H/N/R/P	Wheelbase	51 in. (129.5 cm)
Selectable 2WD / 4WD	Ground Clearance	10.5 in. (26.7 cm)
with Visco-Lok QE auto-locking front differential	Seat Height	34.5 in. (87.7 cm)
Work / Standard / Sport modes Intelligent Engine Braking (iEB)	Rack Capacity	Rear: 35 lb (16 kg)
Tri-Mode Dynamic Power Steering (DPS)	Storage Capacity	N/A
Th-Mode Dynamic Fower Steering (DFS)	Towing Capacity	1,300 lb (590 kg)
	Fuel Capacity	5.4 gal (20.5 L)
Arched double A-arm with sway bar 9.2 in. (23.3 cm) travel	FEATURES	
FOX 1.5 PODIUM† RC2	Gauge	4.5 in. digital display
Torsional Trailing arm Independent (TTI)	Magneto	650 W
9.9 in. (25.1 cm) travel	Instrumentation	DC outlet, 15 A connector
FOX 1.5 PODIUM† RC2	Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights
	Winch	Prewired for available winch
ITP Holeshot <sup>†</sup> ATR 25 x 8/11 x 12 in.	Seat	Standard
12 in. aluminum beadlock	Handlebar	aluminum taper-profile handlebar with full wrap handguards
Duel 014 and die a basine with hardwards to in minter a clinera	Protection	Front bumper
Dual 214 mm disc brakes with hydraulic twin-piston calipers		Front & central skid plate
Single 214 mm disc brake with hydraulic twin-piston caliper	WARRANTY & EXTENDED SERVICE	
	Factory Warranty	1-year BRP limited warranty
	Extended Service	B.E.S.T. term available up to 36 months





Terms