## 2026 OUTLANDER MAX 6X6 BACKCOUNTRY



## PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Selectable 4WD / 6WD with Visco-6Lok<sup>†</sup> front differential
- pDrive primary CVT with work calibration and extra low gear
- Engine modes, Intelligent Engine Braking (iEB™) technology and speed limiter
- 30 in. XPS Iron Force tires with 14 in. aluminum beadlock wheels
- SHOWA gas shocks
- Oversized 4-disc braking system
- Full skid plate, front and rear bumpers, footwell protectors, A-arm protectors, handguards
- 3,500 lb winch with synthetic rope
- RF Digitally Encoded Security System (D.E.S.S.™)
- · Aluminum handlebar with riser
- 1,000 lb bed capacity
- 1,830 lb towing capacity
- LED headlights and taillights, LED signature lights
- Special edition seat with removable passenger seat

Type 101 hp / 69 lb-ft, Rotax* 999 cc V-twin, DOHC, liquid-cooled High flow radiator cooling fan of 120W & 500 cm³  Fuel Delivery System Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)  Transmission pDrive primary CVT with work calibration Extra low L / H / N / R / P  Drive Train Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential  Driving Assistance Work / Standard / Sport modes Intelligent Engine Braking (iEB) Speed limiter  Power Steering Tri-Mode Dynamic Power Steering (DPS)  SUSPENSIONS  Front Suspension Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	FNOINE	10000
High flow radiator cooling fan of 120W & 500 cm³  Fuel Delivery System Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)  Transmission pDrive primary CVT with work calibration Extra low L / H / N / R / P  Drive Train Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential  Driving Assistance Work / Standard / Sport modes Intelligent Engine Braking (IEB) Speed limiter  Power Steering Tri-Mode Dynamic Power Steering (DPS)  SUSPENSIONS  Front Suspension Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	ENGINE	1000R
with Electronic Fuel Injection (EFI)  Transmission  pDrive primary CVT with work calibration Extra low L / H / N / R / P  Drive Train  Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential  Driving Assistance  Work / Standard / Sport modes Intelligent Engine Braking (iEB) Speed limiter  Power Steering  Tri-Mode Dynamic Power Steering (DPS)  SUSPENSIONS  Front Suspension  Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks  SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension  Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks  SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires  XPS Iron Force – 30 x 9 x 14 in. Wheels  VVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Туре	
Extra low L / H / N / R / P  Drive Train  Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential  Driving Assistance  Work / Standard / Sport modes Intelligent Engine Braking (iEB) Speed limiter  Power Steering  Tri-Mode Dynamic Power Steering (DPS)  SUSPENSIONS  Front Suspension  Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks  SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension  Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks  SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires  XPS Iron Force – 30 x 9 x 14 in.  Wheels  14 in. aluminum beadlock  BRAKES  Front  OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Fuel Delivery System	
with Visco-6Lok front differential  Driving Assistance	Transmission	
Intelligent Engine Braking (iEB) Speed limiter  Power Steering Tri-Mode Dynamic Power Steering (DPS)  SUSPENSIONS  Front Suspension Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Drive Train	
SUSPENSIONS Front Suspension Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel Front Shocks SHOWA Internal Floating Piston (IFP) Shocks Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in. Wheels 14 in. aluminum beadlock  BRAKES Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Driving Assistance	Intelligent Engine Braking (iEB)
Front Suspension Arched double A-arm with sway bar 7.5 in. (19.5 cm) travel  Front Shocks SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Power Steering	Tri-Mode Dynamic Power Steering (DPS)
7.5 in. (19.5 cm) travel  Front Shocks SHOWA Internal Floating Piston (IFP) Shocks  Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	SUSPENSIONS	
Rear Suspension Arched double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in. Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Front Suspension	
9 in. (22.9 cm) travel  Rear Shocks SHOWA Internal Floating Piston (IFP) Shocks  TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Front Shocks	SHOWA Internal Floating Piston (IFP) Shocks
TIRES & WHEELS  Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Rear Suspension	
Front / Rear Tires XPS Iron Force – 30 x 9 x 14 in.  Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Rear Shocks	SHOWA Internal Floating Piston (IFP) Shocks
Wheels 14 in. aluminum beadlock  BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	TIRES & WHEELS	
BRAKES  Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Front / Rear Tires	XPS Iron Force – 30 x 9 x 14 in.
Front OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers	Wheels	14 in. aluminum beadlock
twin-piston calipers	BRAKES	
Rear Dual 214 mm disc brakes with hydraulic twin-piston calipers	Front	
	Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

Estimated Dry	1,449 lb (659 kg)
Weight*	100 0 // 50 0 // 50 '
LxWxH	126.9 X 50.2 X 56 in. (322.3 x 127.4 x 142.2 cm)
Wheelbase	93.3 in. (237 cm)
Ground Clearance	13 in. (33 cm)
Seat Height	37.8 in. (96 cm)
Rack Capacity	Front: 120 lb (54.4 kg)
Storage Capacity	Front cargo: 8 gal (30 L) Rear cargo: 58 gal (220 L) Rear undercargo: 6,6 gal (25 L) Total: 72.6 gal (275 L)
Towing Capacity	1,830 lb (830 kg)
Bed Capacity	1,000 lb (454 kg)
Fuel Capacity	5.1 gal (19.5 L)
FEATURES	
Gauge	7.6 in. wide digital display
Magneto	650 W
Instrumentation	Phone storage & USB-C charger
Ignition	RF Digitally Encoded Security System (D.E.S.S.)
Lighting	LED headlights and taillights LED signature
Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable
Seat	Special Edition with removable passenger seat
Handlebar	Aluminum U type (57 mm)
Protection	Heavy-duty front bumper Full skid plate Footwell protectors Front & rear A-arm protectors Handguards
Hitch Type	2 in. hitch receiver
WARRANTY & EXTE	ENDED SERVICE
Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 48 months



