

TECHNICAL SPECIFICATIONS

2027 KTM 350 SX-F

ENGINE

| | |
|----------------------------|---|
| Design | 1-CYLINDER, 4-STROKE ENGINE |
| Displacement | 349.7 CM ³ |
| Transmission | 5-SPEED |
| Fuel-mixture generation | KEIHIN EFI, THROTTLE BODY 44 MM |
| EMS | KEIHIN EMS |
| Clutch primary drive teeth | 72 |
| Primary drive | 24:72 |
| Clutch | WET MULTI-DISC DS CLUTCH, BREMBO HYDRAULICS |
| Engine cylinder | SINGLE CYLINDER |
| Engine stroke | 4-STROKE |

CHASSIS

| | |
|----------------------|---|
| Frame design | CENTRAL DOUBLE-CRADLE-TYPE 25CRM04 STEEL |
| Front brake | DISC BRAKE |
| Rear brake | DISC BRAKE |
| Rear subframe design | ALUMINUM-REINFORCED POLYAMIDE |
| Chain | 520, NON-SEALED |

SUSPENSION

| | |
|-----------------------------|--|
| Front suspension | WP XACT-USD (AER), Ø 48 MM |
| Rear suspension | WP XACT MONOSHOCK WITH LINKAGE |
| Suspension travel (front) | 310 MM |
| Suspension travel (rear) | 300 MM |
| Front suspension adjustment | COMPRESSION (HIGH AND LOW SPEED), REBOUND |
| Rear suspension adjustment | COMPRESSION AND REBOUND ADJUSTABLE |

DIMENSIONS

| | |
|-------------|---------------|
| Seat height | 958 MM |
|-------------|---------------|

| | |
|------------------|---------------|
| Ground clearance | 343 MM |
|------------------|---------------|

| | |
|-------------------------|--------------|
| Tank capacity (approx.) | 7.2 L |
|-------------------------|--------------|

| | |
|-----------------------|-----------------|
| Weight (without fuel) | 102.4 KG |
|-----------------------|-----------------|