

TECHNICAL SPECIFICATIONS

2026 KTM 125 ENDURO R

ENGINE

Design	1-CYLINDER, 4-STROKE ENGINE
Displacement	124.99 CM³
Power	15 PS
Torque	11.5 NM
Transmission	6-SPEED
CO2 emissions	57 G/KM
Cooling	LIQUID COOLED
Engine cylinder	SINGLE CYLINDER
EMS	BOSCH EMS WITH RBW
Engine oil	MOTOREX FORMULA 4T 15W/50
Engine stroke	4-STROKE
Drive type	COMBUSTION

CHASSIS

Front brake disc diameter	285 MM
Front brake disc diameter	11.22 INCH
Rear brake disc diameter	240 MM
Rear brake disc diameter	9.45 INCH
Front brake	BYBRE AXIAL FLOATING CALIPERS WITH 2 PISTONS
Rear brake	BYBRE FLOATING CALIPER 1 PISTON
Chain	520 X-RING
Frame design	STEEL TRELLIS FRAME, POWDER COATED
Steering head angle	62.9 °
Rear subframe design	BOLT ON STEEL TRELLIS FRAME, POWDER COATED
Trail	107 MM
Wheelbase	1475 MM

SUSPENSION

Front suspension	WP APEX OPEN CARTRIDGE 43MM
Rear suspension	WP APEX SPLIT PISTON
Suspension travel (front)	230 MM
Suspension travel (rear)	230 MM
Suspension travel (front)	9.06 INCH
Suspension travel (rear)	9.06 INCH
Front suspension adjustment	NON ADJUSTABLE
Rear suspension adjustment	PRELOAD WITH TOP RING

DIMENSIONS

Seat height	890 MM
Tank capacity (approx.)	9 L
Ground clearance	272 MM
Weight (without fuel)	152 KG
Tank capacity (approx.)	2.38 US GAL
Weight fully fueled	158 KG
Wheels	1.85 X 21"; 2.5 X 18"